

POLYWET RWA

Universal strong wetting and de-aerating agent

Properties

- is compatible with anionic and nonionic products.
- promotes the intensive and rapid penetration of the cotton in dyeing and bleaching processes and also finishing liquors.
- produces very little foam in all liquor processes.
- has extraordinary wetting and emulsifying effect at all temperatures.
- is suitable for using in scouring/washing, desizing, bleaching, dyeing and finishing baths.
- is resistant to acids, alkaline, electrolytes and water hardness at all temperatures.
- can be used in all batch, semi-continuous and continuous equipments.

Field of application

- Substrate** : cellulosic and its blends.
- Aggregate** : all batch, semi-continuous, continuous systems.
- Operation** : rapid wetting and penetrating agent in all processes.

Characteristics

- Type of product** : preparation of fatty alcohol ethoxylate and alkyl-sulfosuccinate
- Ionic nature** : anionic
- Appearance** : clear liquid
- PH of 1% sol.** : Neutral

Application

Dissolving method : can be easily diluted with water.

Guide recipes : It is added to the bath either directly or after pre-dilution with warm water (50°C).

Due to kind of fibers and the processes:

1-3 g/l related to L:R= 1:10 in long baths

3-10 g/l related to pick-up 100% and dry in wet.

Storage stability : 12 months in closed original containers.

The indications given herein correspond to practical experiences. Owing to the differences in local conditions they cannot claim to be complete, so that any liabilities - also with a view to claims of third parties - are excluded.